

Patent claims

1. A method for controlling the electrical battery power which is supplied to or drawn from the battery (5) of a motor vehicle and is coupled to the power supply system of the motor vehicle, the total electrical power (P_g) consumed
5 by the motor vehicle being generated by a generator (3) which is coupled to the internal combustion engine (2) of the motor vehicle,
characterized in that
a cost function is calculated which represents a measure of the additional fuel consumption based on the total electrical power generated by this
10 additional consumption, and in that an optimal value for the battery power is determined such that the cost function is minimized.
2. The method as claimed in claim 1,
15 characterized in that
the battery charging losses (P_v) are taken into account when determining the optimal value.
- 20 3. The method as claimed in claim 2,
characterized in that
the battery charging losses (P_v) are determined by continually averaging the measured efficiency of the battery charging and battery discharging.
- 25 4. The method as claimed in claim 1,
characterized in that
the set battery power is greater than or less than the calculated optimal value in order to keep the state of charge of the battery (5) within a
30 predetermined value range.

5. The method as claimed in claim 1,
characterized in that

regenerative braking of the motor vehicle is carried out in which the braking
energy is converted at least partially to electrical energy.

5

6. The method as claimed in claim 5,
characterized in that

the regenerative braking is carried out in a gear which maximizes the
generated electrical energy.

10

7. A controller for controlling the electrical battery power which is supplied to
or drawn from the battery (5) of a motor vehicle which is coupled to the
power supply system (4) of the motor vehicle, the total electrical power (P_g)
consumed by the motor vehicle being generated by a generator (3) which is
coupled to the internal combustion engine (2) of the motor vehicle,
characterized in that

15

a cost function is calculated which represents a measure of the additional
fuel consumption based on the total electrical power generated by this
additional consumption, and in that an optimal value for the battery power is
determined such that the cost function is minimized.

20